

Remarks

Use only where application and drying can proceed at temperatures above 5°C (preferably above 10°C) and below 35°C. Drying data given is on the assumption that proper ventilation is provided.

Shelf Life

Enviro Prime ME has a shelf life of 2 years if kept in sealed containers in dry store within 0 – 35°C. If stored in high temperature and high humidity locations the shelf life may be reduced. Always mix well by mechanical means before use.

Packaging

1 ltr, 4 ltr and 15 ltr pails. 200 ltr drums available upon request.

Safety Advice

KEEP OUT OF REACH OF CHILDREN.



Manufactured by Waterproofing Technologies Pty Ltd

Address: 295 Princes Highway St Peters NSW 2044 Sydney Australia

Telephone: +61 2 8595 8699

Facsimile: +61 2 8595 8660

Web: www.envirosystems.com.au

Statement of Responsibility

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

Note:

Field service where provided, does not constitute supervisory responsibility. Suggestions made by Enviro Systems either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Enviro Systems are responsible for carrying out procedures appropriate to a specific application.